







#### WATER PROOF SOLUTION





Water-Stopper(Included) A IP-67 water-stopper is added in the end of luminaires as standard assembly which is also an important system for water resistance.

B IP68 Jiffy quick plug/socket connector(Option)

A IP-68 connector is as an optional assembly and ensures that water vapor will not enter into luminaires directly.

Referenced Degree(°)01/2

25°

30°

٩°

15°

**OPTICS** 

**B26** 

B27

### LIGHTING INFORMATION

HOUSING Hard chromeplated molding shaped stainless steel SUS 316L#

FRONT COVER Hard chromeplated stainless steel SUS 316L#

LIGHT WINDOW UVstop & Fireproof PC **CABLE GLAND** Silicone gasket

**GASKET** OPTICS lens. efficiency≥85%

**BRACKET** SUS 316L# NICHIA LED

LED DRIVER Constant Voltage Input, Constant Current Output

CABLE GLAND IP68 PG-11 copper with nickel-coated

PCB Excellent heat conductivity aluminum.coefficient of heat Conductivity≥2.0w/mk POWER CABLE OPTIONAL Outside of luminaire - H07RN-F 2×1.0mm2 with water-stopper, L=1 m, 3 m, 5 m


**BUILT-IN OVERHEAT SENSOR SYSTEM** Automatic Shutdown at  $75^{\circ}\text{C}$ 

Temperature of water between -20°C~40°C less than 1 meter depth APPLICATION ENVIRONMENT

Triac PWM Available 1-10V Dali Customized DIMMING SUPPORT

# ACCESSORIES(Optional)















## **PHOTOMETRIC**

