


CODES: BO-B2XAR0157-IN



Ø: 2.36" (6 cm)



1.7" (4.3 cm)

2.1" (5.4 cm)

Ø: 1.6" (4.3 cm)

LIGHT SOURCE:

1 × 2W OSRAM

LENS::

B33

SELECTED DEEGRE

20°

INPUT VOLTAGE:

110-277V

OPERATING CURRENT:

29 mA

CONSUMPTION:

3.1W

LUMINANCE:

CW=155 | WW=140

IK:

10

FRONT COVER

Hard chromeplated stainless steel SUS 316#

HOUSING

12# Die-casting aluminum dark grey powder coated T=60-80µm Adhesion of ISO class 1/ASTM class 4B

LIGHT WINDOW

Tempered frosted step glass.T=8mm

GASKET

Silicon rubber molding shaped seal

POWER CABLE

Outside of luminaire : 110V/277V: H05RN-F 3×1.0mm², L=0.5m

CABLE GLAND

IP67 Copper and nicked coated

LED TYPE

OSRM SMD3030

CCT

3000K / 3500K / 4000K / 5000K / Custom on request

CRI

90

LED DRIVER

Constant Voltage Input, Constant Current Output

LENS

OPTICS Reflector efficiency≥85%

PCB

Excellent heat conductivity aluminum, coefficient of heat Conductivity≥2.0w/mk

GLASS PRESSURE CAPACITY

Full area=1,106kgs

DIMMING SUPPORT

Triac PWM Available: 1-10V / Dali / Customized

IP

IP67

OPERATING TEMPERATURE

-20°C~40°C

OPTICS

Referenced Degree(°)



B33

9°


15°

20°

45°

60°

WATER PROOF SOLUTION



B Water proof connector IP67(Optional)

sales@gordonbullarda.com

www.bullardoutdoor.com

1-877-964-4646



991 South Gull Lake Dr

Richland, MI 49083

USA

HONEYCOMB LOUVER (Option)



Louver Mh021




- Optional Accessory Honeycomb Louver
- The measured luminous flux data does not contain the honeycomb cover, and the data containing the honeycomb cover is reduced by 20 to 30%.

INSTALLATION DIAGRAM



A: Minimum space for external driver is 48mm.
B: IP67 / 110-277V external high voltage driver.

PHOTOMETRIC



Lux distance cure

Illuminance at a distance		Beam width	
Center beam LUX		V	H
2m 196.35 LUX		0.7m	0.7m
4m 49.09 LUX		1.4m	1.5m
6m 21.82 LUX		2.1m	2.2m
8m 12.27 LUX		2.8m	2.9m
10m 7.85 LUX		3.5m	3.6m
12m 5.45 LUX		4.3m	4.4m

HOW TO ORDER:

CODE:

CODE: BO-B2XAR0157-IN

EXAMPLE:

BO-B2XAR0157-IN-K30-Mh021-DIM-B

BO-B2XAR0157-IN-
K30-Mh021-DIM-B

1.CHOOSE FIXTURE MODEL:

BO-B2XAR0157-IN

2.CHOOSE CCT:

-K30	3000K
-K35	3500K
-K40	4000K
-K50	5000K
-CUS*	Custom on request

3.HONEYCOMB LOUVER (Option)

-Mh021



4.DIMMING OPTIONS:

-PWM	Triac PWM
-DIM	1-10V
-DALI	DALI
-CUS*	Custom on request

5.WATER PROOF SOLUTION (included):

-B Water proof connector IP67 (Option)

