




SMALL (S)



LIGHT SOURCE:

1×8W

LENS:

B71

SELECTED DEGREE:

24°

INPUT VOLTAGE:

110-277V

OPERATION CURRENT:

45 mA

CONSUMPTION:


10 W

LUMINANCE:

792 lm



MEDIUM (M)



LIGHT SOURCE:

4×4W

LENS:

FB11B4

SELECTED DEGREE:

20°

INPUT VOLTAGE:

110-277V

OPERATION CURRENT:

78 mA

CONSUMPTION:

17.4 W

LUMINANCE:

1227 lm







HOUSING 12# Die-casting aluminium finishing or powder painting

T=60-80µm.Adhesion of ISO class 1/ASTM class 4B

CRI 90

CCT 3000K / 3500K / 4000K / 5000K / Custom on request

LIGHT WINDOW Tempered glass.T=4mm

CABLE GLAND IP68 PG-9 PA66

GASKET Tooling shaped seal

BRACKET Powder coated aluminum

POWER CABLE Outside of luminaire

110-277V: H05RN-F 3×1.0mm², L=2.0m

FINISH OPTIONS Dark Grey KAP 7037 Silver Grey KAP 9022 Sanded Black RAL 9005 OPTICS Referenced Degree(°)⊕1/2 B71 15° 24° 33° 45° 60°

15°

20°

30

45°

60°

ACCESSORIES

SPIKE

PC/ABS alloys



l'D	Fitted Item
18B	BO-B3DVU0127-SP
1 <i>7</i> B	BO-B3DWU0460-SF







FB11B4


 I'D
 Fitted Item

 12B
 BO-B3DVU0127-SP

 13B
 BO-B3DWU0460-SP



TREE POLE STRAP










WATER PROOF SOLUTION



A Water-Stopper (Included)

A IP-66 water-stopper is added in the end of luminaires as standard assembly which is also an important system for water resistance.

B IP67 Jiffy quick plug/socket connector (Option)

A IP-67 connector is as an optional assembly and ensures that water vapor will not enter into luminaires directly.

OVERVEW










sales@gordonbullard.com www.bullardoutdoor.com 1-877-964-4646 **C**





991 South Gull Lake Dr Richland, MI 49083




PHOTOMETRIC

















	Illuminanc	e at a	Dista	nce	
Center Beam LUX			Beam Width V H		
2m	1716.93 LUX	7	\	0.7m	0.7m
4m	429.23 LUX	7	\	1.3m	1.3m
6m	190.77 LUX	7	1	2.0m	2.0m
8m	107.31 LUX	Π		2.7m	2.7m
10m	68.68 LUX		\	3.4m	3.3m
12m	47.69 LUX			4.0m	4.0m
V	art Spraad: 10 1			Horiz Spr	-J.10 0



HOW TO ORDER:

CODE:

CODE: BO-B3DVU0127-SP



SMALL(S)

CODE: BO-B3DWU0460-SP



MEDIUM (M)

EXAMPLE:

BO-B3DVU0127-SP-K30-KAP7037-18B-A-B

1.CHOOSE FIXTURE SIZE:

BO-B3DVU0127-SP SMALL BO-B3DWU0460-SP MEDIUM

2.CHOOSE CCT

K30 - 3000K

K35 - 3500K

K40 - 4000K

K50 - 5000K

CUS* - Custom on request

3.BODY FINISH OPTIONS:

-KAP 7037 Dark Grey

-KAP 9022 Silver Grey

-RAL 9005 Sanded Black



HOW TO ORDER:

CODE:

CODE: BO-B3DVU0127-SP



SMALL (S)

EXAMPLE:

BO-B3DVU0127-SP-K30-KAP7037-18B-A-B

4.SPIKE (optional):

STAINLESS STEEL:

-12B BO-B3DVU0127-SP



-13B BO-B3DWU0460-SP

CODE: BO-B3DWU0460-SP



MEDIUM (M)

PC/ABS alloys:

-18B BO-B3DVU0127-SP

-17B BO-B3DWU0460-SP



5. TREE POLE STRAP:

-RD003 BO-B3DVU0127-SP



-RD002 BO-B3DWU0460-SP







HOW TO ORDER:

CODE:





SMALL (S)





MEDIUM (M)

EXAMPLE:

BO-B3DVU0127-SP-K30-KAP7037-18B-A-B

6. WATER PROOF SOLUTION (included):

_A Water-Stopper (Included)

A IP-66 water-stopper is added in the end of luminaires as standard assembly which is also an important system for water resistance.



7. WATER PROOF SOLUTION (optional):

_B IP67 Jiffy quick plug/socket connector (Option)

A IP-67 connector is as an optional assembly and ensures that water vapor will not enter into luminaires directly.

