







FIXTURE TYPE:	
PROJECT NAME:	



### **GENERAL INFORMATION:**

The Bollux Bollard from Bullard Outdoor is an efficient 10W LED solution designed for durability and style in outdoor spaces like gardens, parks, pathways, and villas. Built with robust cement materials, it ensures high IP65-rated protection against corrosion and compression. Operating on 110-277V, this bollard is available in two heights, 17.7" (45 cm) and 29.5" (75 cm), and offers dimming options of 1-10V and non-dimmable settings. With beam angles of 24°, 36°, and 45°, color temperatures ranging from 3000K to 6000K, and CRI options of 80 or 90, Bollux combines reliability with energy efficiency for any outdoor lighting project.

FIXTURE TYPE:	
Bollard	
LIGHTING	
LED	LED
VOLTAGE:	
110-277V	110-
MATERIAL:	
Corrosion-resistant cement	
IP:	
IP 65	IP65









### **BUILT FOR THE STORM**

sales@gordonbullard.com www.bullardoutdoor.com 1-877-964-4646



991 South Gull Lake Dr Richland, MI 49083 USA



HOW	TO ORDER:		CODE:
		4 K30 C00 DIM	BO-1036-BL-H45- B24-K30-C80-DIM
CODE	:: BO-1030-BL-H45-B24	4-K3U-C8U-DIM	) [324 1.00 000 3111]
1	DIMENSIONS:		
	A) Length - B) Width -	L: 5.91" (15 cm) W: 5.51" (14 cm)	
3	HEIGHT:		
	-H45 -H75	H: 17.7" (45 cm) H: 29.5" (75 cm)	
	LIGHT SOURCE:		
	LED / 10W / 650 lr	n	
	BEAM ANGLE:		
	-B24	24°	
	-B36	36°	
	-B45	45°	
5	SPECIFY CCT:		
	-K30	3000K	
	-K40	4000K	
	-K50	5000K	
	-K60	6000K	
6	CRI:		
	-C80	CRI 80	
	-C90	CRI 90	
7	DIMMING OPTION	NS:	
	-NON	NON-Dimmable	
	-DIM	1-10V	
	Examp CODE  1  2  3  4	1 DIMENSIONS:  A) Length - B) Width -  2 HEIGHT:  -H45 -H75  3 LIGHT SOURCE:  LED / 10W / 650 ln  4 BEAM ANGLE:  -B24 -B36 -B45  5 SPECIFY CCT:  -K30 -K40 -K50 -K60  6 CRI:  -C80 -C90  7 DIMMING OPTION -NON	Example: CODE: BO-1036-BL-H45-B24-K30-C80-DIM  1 DIMENSIONS: A) Length - L: 5.91" (15 cm) B) Width - W: 5.51" (14 cm)  2 HEIGHT: -H45 H: 17.7" (45 cm) -H75 H: 29.5" (75 cm)  3 LIGHT SOURCE: LED / 10W / 650 lm  4 BEAM ANGLE: -B24 24° -B36 36° -B45 45°  5 SPECIFY CCT: -K30 3000K -K40 4000K -K50 5000K -K60 6000K  6 CRI: -C80 CRI 80 -C90 CRI 90  7 DIMMING OPTIONS: -NON NON-Dimmable

# **BUILT FOR THE STORM**

sales@gordonbullard.com www.bullardoutdoor.com 1-877-964-4646




991 South Gull Lake Dr Richland, MI 49083 USA




FIXTURE TYPE:			
PROJECT NAME:			


# INSTALLATION INSTRUCTION:




Drill the hole and install the expansion bolts.



Install the mounting base with bolts.



Connect the power supply cable to the lamp with a waterproof(IP68) connector and install the mounting base in.



Install the lamps in mounting

# **BUILT FOR THE STORM**

sales@gordonbullard.com www.bullardoutdoor.com 1-877-964-4646



991 South Gull Lake Dr Richland, MI 49083 USA