







FIXTURE TYPE:	
PROJECT NAME: _	



GENERAL INFORMATION:

The SOLIX Bollard from the Bullard Outdoor range is an outdoor LED bollard light featuring a classic design, offering a power rating of 10W and compatible with 110-277V input voltage. Constructed from pure aluminum and gasket materials, it has a high IP65 protection class, providing excellent resistance to corrosion and compression. This bollard is ideal for various applications, including garden lighting, parks, pathways, and villa projects, and is designed for easy installation with low energy consumption. Available in three sizes, the dimensions are as follows: Small (S) at Ø: 5.9" (15 cm) x H: 15.75" (40 cm), Medium (M) at Ø: 5.9" (15 cm) x H: 23.62" (60 cm), and Large (L) at Ø: 5.9" (15 cm) x H: 39.37" (100 cm). The SOLIX Bollard uses an LED light source rated at 10W with an efficiency of 85 lm/W. It offers a range of correlated color temperatures (CCT) including 2700K, 3000K, 4000K, and 5000K, a beam angle of 120°, and a color rendering index (CRI) of 80 or 90.

Q	
FIXTURE TYPE:	
Bollard	
LIGHTING	
LED	LED
VOLTAGE:	
110-277V	110.
MATERIAL:	
Aluminum	
IP:	
IP 65	IP65
BEAM ANGLE:	



BUILT FOR THE STORM

120°

sales@gordonbullard.com www.bullardoutdoor.com 1-877-964-4646



991 South Gull Lake Dr Richland, MI 49083 USA



FIXTURE TYPE:			
PROJECT NAME:	HOW TO ORDER:		CODE:
	Example: CODE: BO-1301-BL-S-K30-C80-DIM-CUS		BO-1301-BL-S-K30- C80-DIM-CUS
A) Ø5.91" [15cm]	1 MODEL:		
15.75" B)	-S DIMENSIONS: A) Diameter - B) Height -	: Ø: 5.9" (15 cm) H: 15. <i>75</i> " (40 cm)	
A) Ø5.91" [15cm]	-M DIMENSIONS: A) Diameter - B) Height -	: Ø: 5.9" (15 cm) H: 23.62" (60 cm)	
23.62" B)	-L DIMENSIONS: A) Diameter - B) Height -	: Ø: 5.9" (15 cm) H: 39.37" (100 cm)	-
A) Ø5.91"	2 LIGHT SOURCE)
[15cm]	3 SPECIFY CCT:		
39.37" B)	-K27 -K30 -K40 -K50	2700K 3000K 4000K 5000K	,
	4 CRI:		
LED 1110 IP65	-C80 -C90	CRI 80 CRI 90	
LED /110 IP65			

BUILT FOR THE STORM

sales@gordonbullard.com www.bullardoutdoor.com 1-877-964-4646



991 South Gull Lake Dr Richland, MI 49083 USA



FIXTURE TYPE: __ PROJECT NAME: _ A) Ø5.91" [15cm] 15.75" B) A) Ø5.91" [15cm] 23.62" B) A) Ø5.91" [15cm] ^{39.37"} B)

HOW TO ORDER: CODE:

Example:

6

CODE: BO-1301-BL-S-K30-C80-DIM-CUS

BO-1301-BL-S-K30-C80-DIM-CUS

5 DIMMING OPTIONS:

-NON Non-Dimmable

-DIM 1-10V

-DMX DMX512 -RDM RDM

FINISH OPTIONS:

-WH White -BL Black

-CUS Custom on request*

LED (110 IP65)

BUILT FOR THE STORM

sales@gordonbullard.com www.bullardoutdoor.com 1-877-964-4646



991 South Gull Lake Dr Richland, MI 49083 USA