

VIZO Recessed Wall Luminaires Stair / Pathway Luminaires







FIXTURE TYPE:	
PROJECT NAME:	











GENERAL INFORMATION:

The VIZO Recessed Wall Luminaire by Bullard Outdoor is a high-quality LED fixture designed for stair and pathway lighting. Constructed from die-cast dark gray powder-coated aluminum, it combines strength and style with a UV-stable, fireproof PC lens for consistent illumination. Operating on 110–277V, VIZO is rated IP65 for weather resistance and IK10 for impact protection, with an IP67 copper and nickel-coated cable gland ensuring durability. Featuring a stainless steel recessed sleeve, it's available in Sanded Dark Gray, Sanded Black, and Sanded White finishes, offering reliable performance and refined design for modern architectural spaces.

FIXTURE TYPE:

Recessed Wall Luminaires - Stair/Pathway Luminaires

LIGHTING:

LED

VOLTAGE:

110-277V

MATERIAL:

12# Die-casting dark grey powder coated aluminum

LENS:

UVstop & Fireproof PC

CABLE GLAND:

IP67 Copper and nicked coated

RECESSED SLEEVE:

Stainless steel 178#

IP RATING:

IP 65

IP65

LED

IK RATING:

IK 10

FINISHING:

Sanded Dark Gray Sanded Black

Sanded White

sales@gordonbullard.com www.bullardoutdoor.com

1-877-964-4646



991 South Gull Lake Dr Richland, MI 49083

USA



FIXTURE TYPE:	
PROJECT NAME:	HOW TO ORDER: CODE:
NOTES:	Example: CODE: BO-VZ-KPG-RWL-XXX-XXX-XXX-XXX-XXX-XXX BO-VZ-KPG-RWL-D1GA0334-K30-KAP7037-DIM
	1 MODELS:
-D1GA0334 2.75" (7 cm) 1.85" (4.7 cm) 3" (7.5 cm)	CODE -D1GA0334 DIMENSIONS: Length - L: 2.75" (7 cm) Height - H: 3" (7.5 cm) Depth - P: 1.85" (4.7 cm) LIGHT SOURCE: LED / 3 x 0.7W / 48 mA / 36 lm / 110-277V / CRI 80
-D1GB0334 2.75" (7 cm) 1.85" (4.7 cm)	CODE -D1GB0334 DIMENSIONS: Length - L: 2.75" (7 cm) Height - H: 3" (7.5 cm) Depth - P: 1.85" (4.7 cm)
3"	LIGHT SOURCE: LED / 3 x 0.7W / 48 mA / 22 lm / 110-277V / CRI 80
(7.5 cm)	2 CCT OPTIONS: -K30 3000K -CUS Custom on request*
LED (110-) IP65	FINISH OPTIONS: -KAP7037 Sanded Dark Gray -RAL 9005 Sanded Black -RAL9003 Sanded White
	-DIM 1-10V -PWM Pulse Width Modulation -DALI DALI (Digital Addressable Lighting Interface)

sales@gordonbullard.com www.bullardoutdoor.com 1-877-964-4646



991 South Gull Lake Dr Richland, MI 49083 USA



FIXTURE TYPE:		
PROJECT NAME:	HOW TO ORDER: CODE:	
NOTES:	Example: CODE: BO-GL-KPG-RWL-XXX-XXX-XXX-XXX-XXX-XXX-XXX BO-VZ-KPG D1GA0334 KAP7037-	1-K30-
	5 RECESSED SLEEVE: (included) 2.6" (2.66") 3.3" (8.5 cm)	
LED 110. 1P65	0 0 2.55" (6.55 cm)	
	6 FEATURES:	
	• Front cover without screws	
	Use the high-strength clips for fixation. (please refer remark)	
	7 DIAGRAM OF INSTRUCTION:	
	8 PHOTOMATRIC INFO:	
	150 150	litanco

sales@gordonbullard.com www.bullardoutdoor.com 1-877-964-4646



991 South Gull Lake Dr Richland, MI 49083 USA